

ADVANCED ROOF TILE FASTENING SYSTEMS & ACCESSORIES

- Protects Waterproofing by Minimizing Penetrations
- High Wind Resistant
- Earthquake Resistant Absorbs Seismic Energy

STORM-LOCK Tyle-Tye® Hurricane Strap System

This is the preferred system where optimum fastening is required. Tie Wires, Tie Rods or Connectors attach each tile into the Tyle-Tye® Hurricane Strap system fastened to the deck by ring shank nails, screws or spikes. The 1" continuous metallic strip installs under the rows of tile, eliminating any pressure or weight on the strip while maintaining the integrity of the roof system.

S TORM-LOCK Tyle-Tye® Twisted Wire System

This continuous system of Twisted Wire features a special anchor that attaches through the underlayment to wood, concrete, or metal roof decks. Roof tiles are tied to the loops of the twisted wire. The waterproof membrane is punctured only at anchoring points, and the appropriate roofing mastic is used to seal these penetrations.

STORM-LOCK Riness Tile-Tie®

This single piece wire fastening system features a loop and hook fastener that interlocks the tiles. The Riness® Tile-Tie system requires no hand tying of the wires allowing for greater labor and cost savings. It can be used with almost any profile of clay roofing tiles and minimizes penetrations in the underlayment.

S TORM-LOCK Tyle-Tye® Tile Nail

This is a unique fastener used in the cover portion of clay 2-piece mission tile, or clay "S" tile and some concrete roof tiles. Tyle-Tye® Tile Nail outperforms any direct-deck nailed roof tile fastener by securing the tile at two points with one fastener; prevents tile fractures or breaks and uses the uplift forces to drive the nail portion of the fastener deeper into the deck.



Frances Fasteners Inc., dba STORM-LOCK Tile Fasteners 5180 Western Way, Perris, CA 92571
Toll Free 855.383.1011 • Office 951.657.6777 • Fax 951.657.6770 www.storm-locktilefasteners.com